



SN2010-AA-HSC

18 Ports 10/25GbE/4 Ports 40G/100G

Scalable L2 and L3 Ethernet switch

Extended Temperature -30°C ~+60°C

MIL-STD-810 Environment

Vibration Method 514.7, Shock Method 516.7



Key Features

- 2.16T Layer 2 & Layer 3 high-density ToR switches with multi-rate 100GbE ports support 10/25/40/50/100GbE
- Scalable L2 and L3 Ethernet switch with QoS and a full complement of standard-based IPv4 and IPv6 features, including OSPF and BGP routing support.
- L2 multipath support via Virtual Link Trunking (VLT) and Routed VLT support.
- Extensive tunneling capabilities such as IP-in-IP, GRE, MPLS, VXLAN and Geneve.
- Advanced QoS/traffic management feature set such as DCB, RoCE v2 to enable convergence of compute and storage on Leaf/Spine Fabric
- IEEE 1588 v2 timing synchronization Precision Time Protocol (PTP,) on network devices infrastructure
- Support Link Aggregation and LACP (Link Aggregation Control Protocol)
- Increase VM Mobility region by stretching L2 VLAN within or across two DCs with unique VLT capabilities.
- Converged network support for Data Center Bridging, with priority flow control (802.1Qbb), ETS (802.1Qaz), DCBx and iSCSI TLV
- Fully SW and architecture compatibility with Hot-swappable, load-sharing, redundant 110-264 VAC 47~ 63Hz PSUs
- Open Ethernet available with Cumulus, ONIE and SONiC

2 Specifications

SYSTEM

System Power (min/max)	140W/304W
System Operating Temperature range	-30°C ~ +60°C
Storage Temperature range	-40°C ~ +72°C
System Latency	906ns

I/O port

Data plane ports (form factor/quantity)	SFP28/8, QSFP28/3
--	--------------------------

Data plane port config/modes supported	100/50/40/25/10
Connectors	SFP28, QSFP28
OOB port	1/RJ45
Console	1/RJ45 Form Factor
USB I/F	1/Type C (Console)
BMC Port	Optional (Share with OOB)
LEDs (System, Port, etc.)	System, Diag mode, OOB Link, Per PSU connected, Per Port link speed
POWER SUPPLY	
PS Redundant (Y/N)/Quantity	Dual redundant 110~264V AC power supply
PS Input (AC/DC)	AC to DC
PS Input Voltage	110~264V
PS Input Frequency	47-63Hz
PS Efficiency	93%
PS Hot Swappable	YES
FAN	
Fans Redundant/Quantity	YES/4
Fans Reversible (F-R, R-F)	F-R, R-F
Fans Hot Swappable	YES
SOFTWARE	
OCP Compliance	YES
Cumulus	3.7
ONIE support with version	ONIE-2019.05 and Upper
SONiC	201811 and upper
BMC support (Yes/No)	Yes (Optional)
BMC vender/family/model	ASPEED/AST2520

MECHANICAL

Rack-Mountable Width	19 inches
Dimension (W x D x H)	440 x 400 x 44mm
Weight	12kg

3 Appearance

