



# 7SL-3500

3U VPX LIQUID COOLED ATR



- 3U VPX , 3 Payload , Liquid Cooled System
- Custom backplanes with VPX and SOSA aligned slot profiles
- i7-1185GRE processor 4-cores, 2.8 GHz, 28W
- 2 x NVIDIA ® MXM A4500, 16GB, 5888 CUDA
- 32GB DDR4-2666 IB ECC DRAM soldered
- 1 x GLAN, 1 x USB3.0, 1 x DC-IN, 1 x Mini DP, 1 x USB2.0
- DC- IN 18V~36V

# Specifications

## SYSTEM

CPU	Intel® i7-1185GRE processor (Tiger Lake-U), Up to 4 cores (TDP 28W)
Memory type	32GB DDR4-2666 IBECC DRAM soldered
GPU	2 x NVIDIA® MXM A4500, 16GB, 5888 CUDA

## STORAGE

M.2	1 x M.2 2242 512GB NVMe
-----	-------------------------

## SIDE I/O (D38999)

X1	1 x USB3.0
X2	1 x GLAN
X3	1 x USB2.0
X4	1 x MiniDP
DC- IN	1

## OS SUPPORT LIST

OS	Windows 10 (180921H2) , Linux (RHEL 8.6U 20.04.4)
----	---

## THERMAL

Liquid Cooled	Closed-loop evaporative system
---------------	--------------------------------

## MECHANICAL

Power Requirement	18V~36V DC-IN
Dimension	190 x 496 x 269mm (W x D x H)
Weight	23 KG

## Appearance



## Dimension

