



# DUAL DISPLAYS MILITARY CONSOLE

CUSTOM ENGINEERED FOR  
AEROSPACE & DEFENSE



**7STARLAKE**

# MILITARY GRADE PANEL MOUNT DISPLAYS

15"



## Military Grade Smart Display

### ■ SKY15-P20

- ◆ 15" TFT LCD 1024 x 768 (4:3)
- ◆ Intelligent Heater (Options)
- ◆ IP65/ MIL-STD-810 Standards
- ◆ Glass-Film-Glass (GFG) Resistive Touch
- ◆ MIL-DTL-38999 Connector: DC-in; VGA, DVI, USB
- ◆ MIL-STD-461/EMI Filter (Options)
- ◆ Dimension: 412 x 336 x 59mm
- ◆ Sunlight readable Up to 1000 nits

15"



## Military Touch Panel Computer

### ■ Cloud15-PX6

- ◆ 15" TFT LCD 1024 x 768 (4:3)
- ◆ Intelligent Heater
- ◆ IP65/ MIL-STD-810 Standards
- ◆ Intel Core i7 Tiger Lake 11th Gen Processor
- ◆ Glass-Film-Glass (GFG) Resistive Touch
- ◆ MIL-DTL-38999 Connector: DC-in; LAN, Mini-DP, USB
- ◆ MIL-STD-461/EMI Filter (Options)
- ◆ Dimension: 435 x 370 x 65mm
- ◆ Sunlight readable Up to 1000 nits

21"



## Military Grade Smart Display

### ■ SKY21-P04

- ◆ 21.5" TFT LCD 1920 x 1028 (16:9)
- ◆ Intelligent Heater (Options)
- ◆ IP65/ MIL-STD-810 Standards
- ◆ Glass-Film-Glass (GFG) Resistive Touch
- ◆ MIL-DTL-38999 Connector: DC-in; HDMI/DP (Options); USB
- ◆ MIL-STD-461/EMI Filter (Options)
- ◆ Dimension: 520x357x58mm
- ◆ Sunlight readable Up to 1000 nits

24"



## Military Grade Smart Display

### ■ SKY24-P04

- ◆ 23.6" TFT LCD 2560 x 1600 4K (16:9)
- ◆ Intelligent Heater (Options)
- ◆ IP65/ MIL-STD-810 Standards
- ◆ Glass-Film-Glass (GFG) Resistive Touch
- ◆ MIL-DTL-38999 Connector: DC-in; HDMI/DP (Options); USB
- ◆ MIL-STD-461/EMI Filter (Options)
- ◆ Dimension: 580x420x58mm
- ◆ Sunlight readable Up to 1000 nits