





X7-MAX

GPU-POWERED MILITARY LAPTOP
SENSOR-TO-DECISION IN ONE UNIT



- Intel® 13th Gen Core™ i7 Processor
- NVIDIA Quadro A4500
- FHD 1000 Nits Sunlight Readable Multi-touch Display
- Dual 10G Fiber Connectivity
- 2 x PoE Ports, Tactical Camera Support
- Swappable NVMe M.2 Storage
- IP65/MIL-STD-810/461 for Extreme Temperatures, Shock and Vibration
- Extended Temperature -20°C ~+50°C

INTRODUCTION

Military Tough. GPU Smart. Engineered for modern battlefields, 7STARLAKE's 15.6" Military Laptop X7-Max delivers unmatched performance and unyielding versatility. Powered by Intel® 13th Gen Core™ i7 Processor and Nvidia Quadro A4500 GPU, the X7-Max brings high-performance edge computing to mission-critical operations.

With dual 10G SFP+ ports, 2 x PoE, dual 10G fiber connectivity, and swappable NVMe M.2 storage, the ruggedized X7-Max ensures non-stop tactical readiness. Its sunlight-readable multi-touch display, IP65 waterproof housing, and resilience to extreme temperatures make it a reliable asset across land, sea, and air operations. Whether supporting AI-powered decision-making, C4ISR, SIGINT, or UGV/UAV console, the X7-Max is more than a rugged laptop. It's built to meet intelligent warfare.

Appearance



ORDER INFORMATION



Model	X7-PIB50	X7-PIA50	X7-MIA45	X7-MIA45F
CPU	i7-13800HRE	i7-13800HRE	i7-13800HRE	i7-13800HRE
GPU	Blackwell 5000	Ada 5000	A 4500	A 4500
RAM	DDR5 Up to 64GB	DDR5 Up to 64GB	DDR5 Up to 64GB	DDR5 Up to 64GB
TFT-LCD	1000 Nits	1000 Nits	1000 Nits	1000 Nits
Touch	Yes	Yes	Yes	Yes
Storage 1	256 GB	256 GB	256 GB	256 GB
Storage 2	M.2 Option	M.2 Option	M.2 Option	M.2 Option
10G Fiber	N/A	x 2	N/A	x 2
PoE	x 2	N/A	x 2	N/A
LAN	x 2	x 2	x 2	x 2
Rear I/O				
X1	DC-IN	DC-IN	DC-IN	DC-IN
X2	LAN	LAN	N/A	N/A
X3	LAN	LAN	N/A	N/A
X4	3G-SDI (optional)	3G-SDI (optional)	N/A	N/A
X5	3G-SDI (optional)	3G-SDI (optional)	N/A	N/A

SPECIFICATIONS

System	
CPU	Intel® i7-13800HRE (6P+8E/20T, 2.5/5.0GHz, 24MB cache, 65W)
Memory	2 x DDR5 64GB
GPU	NVIDIA® RTX A4500 (7,168 CUDA Cores, 640 GB/s)
Display	
Display	15.6" TFT LCD FHD (1920 x 1080), 1,000 nits brightness display Sunlight readable, resistive multi touch screen Optional: Capacitive multi-touch screen
Operating System	
OS Support	Windows 10 pro Windows 11 Pro
Storage	
Storage	2 x NVMe M.2 storage
Ethernet	
Ethernet	2 x RJ45 2.5 Gigabit
Power	
Power	230W 100-240VAC, 50/60Hz
Dimensions	
Dimensions	395 x 375 x 60 mm (15.55 x 14.76 x 2.36 inch)
Back I/O (Rugged Connector DTL-38999)	
X1	DC-IN
Left I/O	
Left I/O	2 x RS232/ 422/ 485 2 x 10G SFP+ (optional) 1 x Audio Combo Jack
Right I/O	
Right I/O	2 x PoE (optional) 2 x USB 3.0 1 x DP 2 x RJ45
Camera	
Camera	1 x 5M webcam

Wireless	
Wi-Fi (Optional)	Intel® Wi-Fi 6E AX210 WLAN 802.11 a/b/g/n/ac/ax
Bluetooth	Bluetooth 5.3 Ublox M9N GPS/GLONASS/BeiDou/ Galileo
Keyboard	
Keyboard	83-key with backlight, resistive
Rugged Feature	
Rugged Feature	IP65, Aluminum-Magnesium Alloy case, Black or Green Color
Environment	
Operating Temp.	-20°C to +50°C
Permissible Operation Mode	Normal Loading ONLY (No Heavy Loading)
Storage Temp.	-40°C to +71°C
Accessories	
Accessories	AC adapter: 230W 100-240VAC, 50/60Hz MIL-STD-461 AC adapter (230W, 100-240VAC)
MIL-STD-810 Environment Testing Standards	
Method 501, Operational Temperature, high	Procedure II: +60°C, two-hour dwell, four cycles
Method 501, Storage Temperature, high	Procedure I: +75°C, two-hour dwell, four cycles
Method 502, Operational Temperature, low	Procedure II: -40°C, two-hour dwell, four cycles
Method 502, Storage Temperature, low	Procedure I: -40°C, two-hour dwell, four cycles
Method 514, Vibration	Category 24/Non-Operating (Category 20 & 24, Vibration)
Method 514, Vibration	Category 20/Operating (Category 20 & 24, Vibration)
Method 516, Shock	Procedure V Non-Operating (Mechanical Shock)
Method 516, Shock	Procedure I Operating (Mechanical Shock)
Method 507, Humidity	Procedure II: exposure to 10 cycles of 95% relative humidity at temperatures of 30 °C to 60 °C with conformal coating (optional)
Method 500, Altitude (Low	15,000 feet transport, -200÷2500[m] ground operation and exposed to +55°C and -20°C operation (optional)

Pressure)	
Method 510, Sand-Dust	Procedure I: Blasting dust, 12 hours (optional)
MIL-STD-461 ELECTROMAGNETIC TESTING STANDARDS	
CE102	Conducted emissions, power leads, 10KHz to 10MHz
RE102	Radiated emissions, electric filed, 30MHz to 5GHz
RS103	Radiated susceptibility, electric filed, 80Mhz to 3GHz

This datasheet is for marketing purposes only and does not constitute a warranty. All specifications, dimensions, and data are subject to change without notice. For the latest specifications and updates, please contact your 7STARLAKE representatives.